



WICHITA A/C SUPPLY CO
1403 SCOTT
WICHITA FALLS, TX 76301
(940)-322-2466

Mobile Home Furnaces



ELECTRIC

- RE9D10C4** -10 KW M/H DOWNFLOW
- RE9D15C4** -15 KW M/H DOWNFLOW
- RE9D20C4** -20 KW M/H DOWNFLOW

A/C and H/P ready: for up through 4.0 tons
 Built in full sized coil cabinet: no need to add parts
 Built in circuit breakers: for safety and dependability
 Nichrome heating elements: for long lasting efficient heat
 Furnace Warranty: 1 year labor, 2 years parts (10 years heat exchanger parts)

Revolv® RE9 Series Electric Furnace						
Furnace Information	RE9D/U10C4	RE9D/U12C4	RE9D/U15C4	RE9D/U17C4	RE9D/U20C4	RE9D/U23C4
Heating Output (BTUH)*	35,000	41,000	53,000	57,000	70,000	75,000
Total kW (Heating Elements and Blower)	10.4	12.0	15.4	16.6	20.4	22.0
Supply Voltage	240 Volts / 60 Hz / 1-Phase					
Heating Elements, No. (Total kW)	2 (10)	2 (11.6)	3 (15.0)	3 (16.2)	4 (20.0)	4 (21.6)
Blower Wheel Size	10.5" Diameter / 8" Wide					
Motor Speeds, HP Amps	4 Speed, 1/3 HP, 2.9 Amps					
Test ESP (in. w. c.) Max	.3					
Nominal Tonnage Air Volume Range with Factory Installed Blower	2.0 - 4.0 Tons					
Air Filter (Upflow Models)	18" x 20" x 1"					
Air Filter (Downflow Models)	18" x 30" x 1" (Front)			18" x 20" x 1" (Top)		
Furnace Dimensions	20" W x 60.63" H x 24.5" D					

* Heating output rated a listed voltage. For outputs at voltages other than 240V, multiply the BTUH rating by the following factors: x 0.92 (230V), x 0.84 (220V, x 0.75 (208V)



WICHITA A/C SUPPLY CO
1403 SCOTT
WICHITA FALLS, TX 76301
(940)-322-2466

Mobile Home Furnaces



GAS

- RG1D56N4 -56 BTU 80% M/H W/O COIL CABINET**
- RG1D70N4 -70 BTU 80% M/H W/O COIL CABINET**
- RG1D90N4 -90 BTU 80% M/H W/O COIL CABINET**

Furnace Model Number	Description	Depth (D)	Width (W)	Height (H)	Input MButh	Output MButh	Orifice# Ntl Gas	Orifice# LP Gas	A/C Ready Tons	Shipping Weight (lbs)
RG1D56N3	Gas-80%, Downflow, 56KBTU no cabinet, 3 Ton blower*	23-3/4"	19-7/8"	56"	56	46	29	45	3	152
RG1D70N3	Gas-80%, Downflow, 70KBTU no cabinet, 3 Ton blower*	23-3/4"	19-7/8"	56"	70	57	24	42	3	153
RG1D77N3	Gas-80%, Downflow, 77KBTU no cabinet, 3 Ton blower*	23-3/4"	19-7/8"	56"	77	62	21	40	3	149
RG1D90N3	Gas-80%, Downflow, 90KBTU no cabinet, 3 Ton blower*	23-3/4"	19-7/8"	56"	90	72	17	36	3	151
RG1D56C3	Gas-80%, Downflow, 56KBTU w/cabinet, 3 Ton blower	23-3/4"	19-7/8"	76"	56	46	29	45	3	167
RG1D70C3	Gas-80%, Downflow, 70KBTU w/cabinet, 3 Ton blower	23-3/4"	19-7/8"	76"	70	57	24	42	3	168
RG1D77C3	Gas-80%, Downflow, 77KBTU w/cabinet, 3 Ton blower	23-3/4"	19-7/8"	76"	77	62	21	40	3	164
RG1D90C3	Gas-80%, Downflow, 90KBTU w/cabinet, 3 Ton blower	23-3/4"	19-7/8"	76"	90	72	17	36	3	166
RG1D56N4	Gas-80%, Downflow, 56KBTU no cabinet, 4 Ton blower*	23-3/4"	19-7/8"	56"	56	46	29	45	4	156
RG1D70N4	Gas-80%, Downflow, 70KBTU no cabinet, 4 Ton blower*	23-3/4"	19-7/8"	56"	70	57	24	42	4	157
RG1D77N4	Gas-80%, Downflow, 77KBTU no cabinet, 4 Ton blower*	23-3/4"	19-7/8"	56"	77	62	21	40	4	156
RG1D90N4	Gas-80%, Downflow, 90KBTU no cabinet, 4 Ton blower	23-3/4"	19-7/8"	56"	90	72	17	36	4	156
RG1D56C4	Gas-80%, Downflow, 56KBTU w/cabinet, 4 Ton blower	23-3/4"	19-7/8"	76"	56	46	29	45	4	172
RG1D70C4	Gas-80%, Downflow, 70KBTU w/cabinet, 4 Ton blower	23-3/4"	19-7/8"	76"	70	57	24	42	4	173
RG1D77C4	Gas-80%, Downflow, 77KBTU w/cabinet, 4 Ton blower	23-3/4"	19-7/8"	76"	77	62	21	40	4	169
RG1D90C4	Gas-80%, Downflow, 90KBTU w/cabinet, 4 Ton blower	23-3/4"	19-7/8"	76"	90	72	17	36	4	171

*For cooling and heat pump applications on no cabinet models, add coil cabinet 91196A (20") or 922594 (26")