



**WICHITA A/C SUPPLY CO**  
**1403 SCOTT**  
**WICHITA FALLS, TX 76301**  
**(940)-322-2466**



## DX-TREME CM SERIES UNCASSED DOWNFLOW COILS

### Standard Specifications

- Rifled copper tubing, enhanced aluminum fins
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed
- Left-hand refrigerant and plumbing connections
- Liquid line -3/8" ODS, suction line – 3/4" ODS pn 1-1/2 – 3 ton & 7/8" ODS on 3-1/2 – 5 ton
- Liquid line Schrader valve for hiss-testing
- Heavy duty polypropylene drain pans
- Condensate drain elbow and flexible drain tubing included
- Downflow plate kit included
- AHRI certifiable with all brands of A/C and heat pump systems



COIL MODEL	PISTON SIZE		DIMENSIONS		
	R22	R410a	PAN WIDTH	PAN DEPTH	BARE SLAB HEIGHT
CM36A[2,3]-177L	0.074	0.068	17-3/4	19-5/8	17-1/2
CM48E3-177L	0.084	0.08	17-3/4	19-5/8	19-1/2

## DX-TREME CE SERIES CASSED MULTI-POSITION COILS

### Standard Specifications

- Rifled copper tubing, enhanced aluminum fins
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed
- Left or right-hand refrigerant and plumbing connections
- Liquid line -3/8" ODS, suction line – 3/4" ODS pn 1-1/2 – 3 ton & 7/8" ODS on 3-1/2 – 5 ton
- Externally mounted flowrater body with Schrader valve for hiss-testing
- Heavy duty plastic upflow drain pans on most models, powder coated galvanized steel horizontal drain pans standard on all
- Upflow, horizontal right, or horizontal left without field modification. Downflow applications require plate kit, included.
- Split access doors in front for easy service
- Fully insulated cabinets with faced insulation
- AHRI certifiable with all brands of A/C and heat pump systems



COIL MODEL	PISTON SIZE		DIMENSIONS				
			CABINET WIDTH		CABINET DEPTH	CABINET HEIGHT	
	R22	R410a	MIN WIDTH	MAX WIDTH			
CE24A	0.059	0.055	14	23	21-1/2	19	
CE36A	0.074	0.068	14 (2&3R), 17 (4R)		23	21-1/2	23
CE48A	0.084	0.08	17	26-1/2	21-1/2	27	
CE60A	0.092	0.089	20-1/2	26-1/2	21-1/2	30	